



# Hygiene Monitor – MMD9000 series

## Stainless steel monitor solution for hygienic environments

Fully closed stainless steel housing, without screws and edges, optimised for high hygienic requirements: The monitor of ADS-TEC has been developed and designed for machine and system operation in sensitive hygiene environments.



### Easy to assemble

- > Three mounting options are available:
  - > Direct mounting (with optional spacer)
  - > VESA adapter
  - > Rotatable tube adapter for 48 mm support arm systems

- > Foot or support arm mounting optional
- > Horizontal or vertical alignment possible
- > Compact design for convenient usage

### Easy to clean

- > Standard cleaning agents can be used
- > Easy to wipe and clean
- > Preventing dirt and bacteria thanks to a screwless design without joints and edges

# Technical Data

## MMD9016

<b>Display</b>	15.6" TFT LED backlight Full HD 1920 x 1080 pixels Typical brightness: 400 cd
<b>Housing</b>	Fully closed stainless steel housing
<b>Touch</b>	PCAP multi-touch / tempered glass Optional: Shatter protection film
<b>Interfaces</b>	1 x USB 2.0 Type A 1 x DisplayPort or 1 x USB 2.0 Type A 1 x HDMI
<b>Power adapter</b>	24 VDC (tolerance 18 - 30 VDC)
<b>Protection class</b>	IP69K
<b>Operating temperature</b>	0 °C to +45 °C
<b>Humidity</b>	10 to 85% non-condensing
<b>Dimensions (W x H x D)</b>	370 x 239 x 33 mm (without adapter)
<b>Weight</b>	4.5 kg (without adapter)

